



ALUMINIUM BI-FOLDING DOORS QUOTE REQUEST

Full Name: _____ Company: _____
 Address: _____
 _____ Postcode: _____
 Telephone: _____ Fax: _____
 Mobile: _____ Email: _____

Site Delivery Postcode: _____ Job Reference: _____
**glass delivery surcharge may apply*
 Products must comply to thermal and ventilation performance requirements in line with current Document L and F Legislation.
 MFT supply compliant product for both New Build and Renovation products.

***Project installation type:** (**compulsory field*) New Build Renovation / Replacement

Indicates sash direction Width: _____ Height: _____
including cill

→

Viewed from the outside

Minimum sash width: 600mm*. Maximum sash width: 1250mm. Max height: 2500mm
**Minimum door width of 600mm only available on configurations with a traffic door, otherwise 700mm minimum sash width applies*

Glazing: (28mm units)

New Build Compliant
 U 1.1 Clear Laminated

Renovation / Replacement Compliant
 Clear Toughened
 Clear Laminated

Buyer responsible for compliance
 Unglazed

Integral blind glass options

Renovation / Replacement Compliant
Centre pane U=1.2 W/m²K
 28mm clear low E
 Laminated with clear low E (PAS24)

New Build Compliant
Centre pane U=1.0 W/m²K
 Laminated with solar control

Slat colours

<input type="checkbox"/> S102 White*	<input type="checkbox"/> S155 Grey
<input type="checkbox"/> S106 Yellow	<input type="checkbox"/> S156 Metallic silver
<input type="checkbox"/> S120 Agate Grey	<input type="checkbox"/> S157 Silver*
<input type="checkbox"/> S125 Beige	<input type="checkbox"/> S158 Slate grey
<input type="checkbox"/> S130 Green	<input type="checkbox"/> S159 Anthracite grey
<input type="checkbox"/> S142 Light blue	<input type="checkbox"/> S159 Anthracite grey / S102 White
<input type="checkbox"/> S149 Cream*	<input type="checkbox"/> B160 Black

**When the laminated glass option is chosen the only slat colours available are S102 White, S149 Cream & S157 Silver*

Slider, sideguide & headrail colour

White Beige Black
 Light grey Anthracite grey

**When the laminated glass option is chosen only slider, sideguide & headrail colours available are White, Beige & Light Grey*

Operation magnet position
 when viewed from the inside

Left side of sash
 Right side of sash

Standard colours

<input type="checkbox"/> White - Gloss (RAL 9910)	<input type="checkbox"/> Anthracite Grey - Matt (RAL 7016)	<input type="checkbox"/> Black - Matt (RAL 9005)	<input type="checkbox"/> Agate Grey - Matt (RAL 7038)
<input type="checkbox"/> Agate Grey - Matt, external (RAL 7038) / White - Gloss, internal (RAL 9910)	<input type="checkbox"/> Black - Matt, external (RAL 9005) / White - Gloss, internal (RAL 9910)		
<input type="checkbox"/> Anthracite Grey - Matt, external (RAL 7016) / White - Gloss, internal (RAL 9910)			

Special colours RAL / BS + finish

External RAL/BS colour:	<input type="checkbox"/> Satin <input type="checkbox"/> Matt	Internal RAL/BS colour:	<input type="checkbox"/> Satin <input type="checkbox"/> Matt
	<input type="checkbox"/> Gloss		<input type="checkbox"/> Gloss

Threshold

Standard
 150mm Integrated cill threshold (open out only)

Opening

Open in Open out

Notes

Outside access unavailable without a traffic door.
 We do not offer a wheelchair specific threshold option.
 PAS 24 as standard

Cill

None 100mm
 150mm 190mm

Frame extender

20mm 40mm

Top
 Left Right

Trickle vent (s)

1 2 3 4

Frame extender not required for trickle vents
***2667mm² airflow per vent**
Buyer is responsible for ensuring Doc F ventilation compliance.

Furniture

White Black Chrome
 Grey Brushed stainless steel
 Grey/White Black/White

Delivery

Assembled Kit form

Note:
 Please ensure that the purchasing company have sufficient able bodied representatives available at the delivery address to assist with the offloading of the products. If this is not met you may be charged for re-delivery of both product and glass



Email quote to: sales@madefortrade.co Tel: 01642 610799